

ViewSonic® PROJECTOR **PJD7526w**

Key Features

SuperColor™ Technology: Best in Class
Color Accuracy | Bright Images Less
lighting limitations | ViewSonic Exclusive
RGBCYW Color Wheel Empowers
LightStream™ Projectors | SonicExpert™
Technology Clear, comfortable, and louder
sound over same-class projectors |
SonicMode Optimized audio performance
for Speech, Entertainment, or Standard
scenario



Product Description

The ViewSonic networkable LightStream™ PJD7526w WXGA projector with a sleek black chassis, features 4,000-ANSI Lumen, majestic style, intuitive design and impressive audiovisual performance. Exclusive SuperColor™ technology offers a RGBCYW color wheel - 120% brilliant color, for true-to-life image projection, while SonicExpert™ technology powers a 10W cube speaker to deliver incredibly clear and audible sound. PortAll™ - a neatly designed enclosed HDMI/MHL connection compartment, supports wireless HDMI dongles or MHL connectors, while a cable management hood eliminates unsightly cable clutter. With a smart design, the PJD7526w is the ideal projector in any environment with less lighting limitations.

Visit Us - www.viewsonic.com

DISPLAY

Resolution:	1280x800 (WXGA)
F Stop / Focal Length:	2.56 ~ 2.68 / 22 ~ 24.1
Zoom Factor:	1.1x
Focus / Zoom:	Manual / Manual
Keystone:	+/- 30° (Horizontal / Vertical)
Display Size:	30" ~ 300"
Throw Distance:	1.00 m ~ 10.98 m
Throw Ratio:	1.55 ~ 1.7
Lamp Power:	240 W
Lamp Life (Normal /SuperEco mode):	3,500 / 6,500 (hours)
Brightness:	4,000 ANSI Lumens
Contrast Ratio:	22,000 :1
Color Depth:	1.07 Billion Colors (30 bits per color)
Optical Offset:	100 % +/-5%

AUDIO

Speaker:	10W Cube x1
----------	-------------

INPUT SIGNAL

Video:	480i and 576i, 480p and 576p, 720p, 1080i, 1080p
Frequency:	15 ~ 100 KHz / 24 ~ 120 Hz

COMPATABILITY

PC:	Support up to 1920x1080@60Hz
Mac:	Support up to 1920x1080@60Hz

CONNECTOR

VGA Input:	x2
VGA Output:	x1
Digital Input:	HDMI (1.4a) x1 / HDMI (MHL2.0) x1
Composite Input:	RCA x1
S-Video Input:	x1
Component:	x2 (Share with VGA input)
Audio Input:	3.5mm mini jack x2
Audio Output:	3.5mm mini jack x1
Microphone in:	Share with Audio in 2 connector
Control:	RS-232
USB:	Mini type B x1 (Maintenance and mouse control)
Lan:	RJ-45

POWER

Voltage:	100~240Vac 50/60Hz (Auto Switching)
Power Consumption:	350 W (Max.)

OPERATING CONDITION

Temperature:	0°C ~ 40°C (32°F ~ 104°F)
Humidity:	0% ~ 90% (non-condensing)

NOISE LEVEL

Normal / Eco Mode:	36dB / 31dB
--------------------	-------------

DIMENSIONS

Physical:	316 x 228 x 103.7 mm
-----------	----------------------

WEIGHT

Net:	2.5 kgs / 5.51 lbs
------	--------------------

REGULATIONS

Mexico Energy test/Registration, TUV-S Mark(Argentina), India BIS, FCC,CE EMC,CB,CCC, ROHS, REACH, SVHC, WEEE, ErP, cTUVus, Mexico NOM, KC, PSB, CECP, RCM

PACKAGE CONTENTS

Power Cord / VGA Cable / Remote Control with Batteries (With Laser pointer) / Quick Start Guide / ViewSonic CD Wizard /Cable Management