

ViewSonic® PROJECTOR

Pro8530HDL

Key Features

Utilize Unique "Flex-In" Design Flexible Integration | Easy-Access Top Cover Ample space for maintenance | PortAll®: Secure MHL/HDMI port with built-in Micro USB cable Big dongle compartment | Cable Management Hood Neat exterior | 4-in-1 Power Button Easy-on control



Product Description

Utilizing a unique "Flex-In" design, the Pro8530HDL integrates an intuitive form, high flexibility and an easy installation process, making it the ideal installation projector. Equipped with 5,200 ANSI Lumens and Full HD resolution, the Pro8530HDL boasts a sleek top cover and an intuitive PortAll® compartment to accommodate HDBT, wireless dongle, or PC stick integration for versatile application, while the cable management and 4-in-1 power button embody a bold and futuristic design. Moreover, the 4 HDMI ports, and centered lens with multiple adjustment in vertical lens shift, 1.6x optical zoom, HV keystone (auto V), and 4-corner offer flexible and easy installation. Powered by SuperColor™ and SonicExpert®, the Pro8530HDL provides a professional audiovisual performance. The Pro8530HDL not only meets large venue Pro AV projection requirements, but is also more than enough for general high-brightness projection.

Visit Us  www.viewsonic.com

DISPLAY

Type:	TI DMD 0.65
Resolution:	1920x1080 (Full HD)
F Stop / Focal Length:	2.54~3.07 / 15.75mm ~ 25.1mm
Optical Zoom:	1.6X
Keystone:	+/- 30° (Horizontal / Vertical)
Auto keystone:	Yes (Vertical)
Lens Shift:	Yes (7.5% Full high or 15% Half high)
Display Size:	30" ~ 300"
Throw Distance:	0.71 m ~ 11.36 m
Throw Ratio:	1.07~1.71
Lamp Power:	370W
Lamp Life (Normal / SuperEco Mode):	2,000 / 2,500 (hours)
Brightness:	5200 ANSI Lumens
Contrast Ratio:	5000:1
Normal / Eco Mode:	36dB / 33dB
Optical Offset:	115%~130%+-5%

AUDIO

Speaker:	10W Cube x 2
----------	--------------

INPUT CONNECTIVITY

HDMI/MHL:	x1
HDMI:	x3
VGA:	x2
S-Video:	x1
Component:	x2 (Share with VGA input)
Composite:	RCA x1
Audio:	3.5mm mini jack x2, RCA(L/R) x1
USB:	Type A x1 (Power Charging) / Mini type B x1 (Maintenance and mouse control) / Micro USB Wire x1 (Power Charging)
Microphone:	Share with Audio in 2 connector

OUTPUT CONNECTIVITY

VGA:	x1
Audio:	3.5mm mini jack x1
DC Output:	x1

OTHER CONNECTIVITY

Lan RJ-45:	x1
3D VESA:	x1
IR Connector:	x1

CONTROL

RS232:	x1
--------	----

DIMENSIONS

Physical (W×H×D):	469.5 x 316.24 x 139.8 mm
-------------------	---------------------------

WEIGHT

Net:	6.3 kgs / 13.89 lbs
------	---------------------

POWER

Voltage:	100~240Vac 50/60Hz
Power Consumption:	574 W (Max.)

REGULATIONS

Mexico Energy test/Registration, EAC, TUVS Mark(Argentina), India BIS, FCC,CE , EMC,CB, CCC, ROHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, PSB, RCM, CECP

PACKAGE CONTENTS

Power Cord / VGA Cable, 1.8m, black / Remote Control with Batteries (With Laser pointer) / Quick Start Guide / ViewSonic CD Wizard / Cable Cover