

# ViewSonic® PROJECTOR **PJD5351LS**

## Key Features

Bright Images Anywhere | Immersive 3D Viewing | True-to-life Color | The Perfect Fit for Small Spaces | Versatile Connectivity



## Product Description

The ViewSonic PJD5351LS XGA short throw projector features 3,300 ANSI lumens and 22,000:1 contrast ratio to offer impressive visual performance. ViewSonic's exclusive SuperColor™ technology offers wide gamut color coverage that produces true-to-life image color. With 0.61 short throw, 100" images can be projected onto the projection screen from only 1.24 meters away, keeping the projection beam on the screen and off of the presenter, preventing distracting shadows from being cast onto the projection screen. The extensive connectivity including dual computer in port and 1 monitor out port, allowing users to connect to a variety of HD devices or additional displays to satisfy the diverse needs. PJD5351LS also comes with energy-saving SuperEco mode which reduces power consumption and extends the lamp life by up to 10,000 hours, reducing the frequency of lamp replacement and lower the replacement costs.



Visit Us  [www.viewsonic.com](http://www.viewsonic.com)

**SPECIFICATION**

Projection system:	0.55" XGA
Native Resolution:	1024x768
DC type:	DC3
Brightness:	3300 ANSI lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/10000
Lamp Watt:	190W
Lens:	F=2.6, f=6.9mm
Projection Offset:	130%+/-5%
Throw Ratio:	0.61
Image size:	60" - 180"
Throw Distance:	0.74m-2.23m (100" @ 1.24m)
Keystone:	±40° (Vertical)
Optical Zoom:	Fixed
Audible Noise (Eco):	32dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	48~120Hz

**INPUT**

Computer in (share with component):	2
Audio-in (3.5mm):	1

**OUTPUT**

Monitor out:	1
Audio out (3.5mm):	1

**CONTROL**

RS232:	1
USB type mini B (Services):	1

**OTHERS**

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.5kg
Dimensions (WxDxH) w/adjustment foot:	316x228x104mm
Language:	English, France, Spanish, Thai, Korea, Germany, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic

**STANDARD ACCESSORY**

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	1
Lens Cover:	1