

ViewSonic® PROJECTOR

Pro8510L

Key Features

Utilize Unique "Flex-In" Design Flexible Integration | Easy-Access Top Cover Ample space for maintenance | PortAll®: Secure MHL/HDMI port with built-in Micro USB cable Big dongle compartment | Cable Management Hood Neat exterior | 4-in-1 Power Button Easy-on control



Product Description

Utilizing a unique "Flex-In" design, the Pro8510L integrates an intuitive form, high flexibility and an easy installation process, making it the ideal installation projector. Equipped with 5,200 ANSI Lumens and XGA resolution, the Pro8510L boasts a sleek top cover and an intuitive PortAll® compartment to accommodate HDBT, wireless dongle, or PC stick integration for versatile application, while the cable management and 4-in-1 power button embody a bold and futuristic design. Moreover, the 4 HDMI ports, and centered lens with multiple adjustment in vertical lens shift, 1.6x optical zoom, HV keystone (auto V), and 4-corner offer flexible and easy installation. Powered by SuperColor™ and SonicExper®, the Pro8510L provides a professional audiovisual performance. The Pro8510L not only meets large venue Pro AV projection requirements, but is also more than enough for general high-brightness projection.

Visit Us  www.viewsonic.com

DISPLAY

Type:	TI DMD 0.55
Resolution:	1024x768 (XGA)
F Stop / Focal Length:	2.54~3.07 / 15.75mm ~ 25.1mm
Optical Zoom:	1.6X
Focus / Zoom:	Manual / Manual
Keystone:	+/- 30° (Horizontal / Vertical)
Auto keystone:	Yes (Vertical)
Lens Shift:	Yes (7.5% Full high or 15% Half high)
Display Size:	30" ~ 300"
Throw Distance:	0.86 m ~ 13.72 m
Throw Ratio:	1.41 ~ 2.25
Lamp Power:	370W
Lamp Life (Normal /Super Eco mode):	2,000 /2,500 (hours)
Brightness:	5200 ANSI Lumens
Contrast Ratio:	5,000:1
Optical Offset:	115%~130%+-5%
Aspect Ratio:	4:3 ; 16:10
Color Depth:	1.07 Billion Colors (30 bits per color)

AUDIO

Speaker:	10W Cube x 2
----------	--------------

INPUT SIGNAL

Frequency:	15 ~ 100 KHz / 24 ~ 120 Hz
------------	----------------------------

COMPATABILITY

PC:	Support up to 1920x1080@60Hz
Mac:	Support up to 1920x1080@60Hz

CONNECTOR

VGA Input:	x2
VGA Output:	x1
Digital Input:	HDMI x3 / HDMI (MHL2.0) x1
Composite Input:	RCA x1
S-Video Input:	x1
Component:	x2 (Share with VGA input)
Audio Input:	3.5mm mini jack x2, RCA(L/R) x1
Audio Output:	3.5mm mini jack x1
Microphone in:	Share with Audio in 2 connector
Control:	RS-232
USB:	Type A x1 (Power Charging) / Mini type B x1 (Maintenance and mouse control) / Micro USB Wire x1 (Power Charging)
Lan:	x1
3D VESA:	x1
DC Output:	x1
IR connector:	x1

POWER

Voltage:	100~240Vac 50/60Hz (Auto Switching)
Power Consumption:	574 W (Max.)
Standby:	<0.5W

OPERATING CONDITION

Temperature:	0°C ~ 40°C (32°F ~ 104°F)
Humidity:	0% ~ 90% (non-condensing)

NOISE LEVEL

Normal / Eco Mode:	36dB / 33dB
--------------------	-------------

DIMENSIONS

Physical:	469.5 x 316.24 x 139.8 mm
-----------	---------------------------

WEIGHT

Net:	6.3 kgs / 13.89 lbs
------	---------------------

REGULATIONS

"Mexico Energy test/Registration, EAC, TUVS Mark(Argentina), India BIS, FCC,CE EMC,CB,,CCC, ROHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, PSB, RCM, CECP"

PACKAGE CONTENTS

Power Cord / VGA Cable / Remote Control with Batteries (With Laser pointer) / Quick Start Guide / ViewSonic CD Wizard / Cable Cover