

ViewSonic® PROJECTOR **PJD5353LS**

Key Features

SuperColor™: Best in Class Color Accuracy
| Short Throw | 3D Blu-ray Ready HDMI |
Color Mode Best view modes |
SonicExpert™ Technology



Product Description

The ViewSonic LightStream™ PJD5353LS is designed with elegant style and audiovisual performance. A short throw lens with a 0.61 throw ratio offers large projection images for smaller rooms. This white projector makes a big statement with its elegant curves and light beam shape. Its thoughtful design, which includes a tactile keypad, instructional icons, and non-slip foot pads, also presents an intuitive and user-friendly interface. With SuperColor™ 6-Segment Color Wheel maximizes color saturation and brightness for true-to-life image projection. The LightStream Projector PJD5353LS is also powered by SonicExpert™ technology; the built-in speaker surpasses competing products in sound clarity and volume performance, as well as comfort. The LightStream Projector PJD5353LS boasts HDMI connectivity and native XGA resolution. It provides digital high definition devices, supporting media-rich business and education presentations. The HDMI delivers single-cable transmission of image and sound signals, for a more convenient installation process. The 3,200 ANSI Lumens lamp with a 22,000:1 contrast ratio is for clearer and brighter images. From small to medium meeting rooms or classrooms, LightStream Projector PJD5353LS delivers quality images in brightness and colors. Supporting 2 x VGA, Composite Video, S-Video, 1 x VGA output, Audio in/out, Mini USB and RS232, this projector has flexible connectivity with analog-based equipment, providing compatibility with conventional analog-based applications without adapters or converters. DynamicEco® further reduces power consumption by up to 70% and extends the lamp life by up to 10,000 hours.

Visit Us ■ www.viewsonic.com

DISPLAY

Resolution:	1024x768
Lens:	Optical Zoom: Fixed; Digital Zoom: 0.8X~2.0X
Size:	50 - 250 inch
Throw Distance:	0.37 m - 3.72 m
Throw Ratio:	0.6
Lamp:	190W
Lamp Hours (Nor/SuperEco):	5000/10000
Brightness:	3200 ANSI Lumens
Contrast Ratio:	22,000:1 (DynamicEco Mode)
Keystone Correction:	Vertical: +40~-40°, (Manual)
Aspect Ratio:	4:3
Color Depth:	1.07 Billion Colors (30 bits per color)
Optical Offset:	130 % +/-5%

AUDIO

Speakers:	2W Cube x 1
-----------	-------------

INPUT SIGNAL

Video:	NTSC: NTSC M (3.58 MHz), 4.43MHz PAL: PAL (B, D, G, H, I, M, N, 60) SECAM: SECAM (B, D, G, K, K1, L) SD: 480i and 576i ED: 480p and 576p HD: 720p, 1080i, 1080p
Frequency:	Fh: 15-102KHz; Fv: 23-120Hz

COMPATIBILITY

PC:	1024x768@60Hz (native)
Mac:	1024x768@60Hz (native)

CONNECTOR

RGB Input:	VGA Input x2
RGB Output:	VGA Output x1
Composite Video:	RCA-1 x1
S Video:	Mini-Din 4 pin x1
Component Video:	Share with VGA (x2)
Digital:	HDMI 1.4 x 1
Audio:	3.5mm Mini-Mono Jack x1
Control:	RS232 (DB-9) x1
USB:	Mini USB x1 (For Mouse control & firmware upgrade)

POWER

Voltage:	100~240Vac 50/60Hz (Auto Switching)
Consumption:	265 W Max

OPERATING CONDITIONS

Temperature:	32°~104°F / 0°~40°C
Humidity:	10~90%, Non-Condensation

DIMENSIONS

Physical:	316mm (width) x 103.7mm (height) x 228mm (depth)
-----------	--

WEIGHT

Net:	2.5 kg
------	--------

REGULATIONS

CB, TUV-GS, UL/cUL, FCC (including ICES-003), CE,C-Tick, Mexico Energy test/Registration, EAC, UkrSEPRO/EMC DOC, UL COC, TUV-S Mark(Argentina), PSB, KCC, KC, SASO, CCC, BIS, WEEE, RoHS, REACH, SVHC, ErP

PACKAGE CONTENTS

Power Cord, 1.8m, black x1
VGA Cable, 1.8m, black x 1
Remote Control with Batteries (Without Laser)
Quick Start Guide (one sheet version), x1
ViewSonic CD Wizard (w User Manual) x 1
Lens Cap