

ViewSonic® PROJECTOR **PJD7720HD**

Key Features

SuperColor™ Technology: Best in Class
Color Accuracy | PortAll™: Enclosed
HDMI/MHL Dongle Compartment A clean
look | ViewSonic Exclusive RGBCYW Color
Wheel Empowers LightStream™ Projectors
| Auto Power On Instant activation upon
signal connection | Smart Restart Instant
reactivation during presentation



Product Description

The ViewSonic LightStream™ PJD7720HD 1080p valued projector features 3,200 ANSI Lumens, Full HD 1920 x 1080 native resolution, an intuitive, user-friendly design and a sleek chassis. Exclusive SuperColor™ technology offers a 6-Segment Color Wheel - 120% brilliant color, for true-to-life image projection, while SonicExpert™, ViewSonic's proprietary sound enhancement technology, powers a 10W cube speaker to deliver incredibly clear and audible sound. PortAll™ - a neatly designed enclosed HDMI/MHL connection compartment, supports wireless HDMI dongles or MHL connectors. With a smart design, the PJD7720HD is the ideal projector for high definition presentations.

Visit Us - www.viewsonic.com

DISPLAY

Resolution:	1920x1080 (Full HD)
F Stop / Focal Length mm:	2.59 ~ 2.87 / 16.88 ~ 21.88
Zoom Factor:	1.1x
Focus / Zoom:	Manual / Manual
Keystone:	+/- 40° (Vertical)
Display Size:	30" ~ 300"
Throw Distance:	0.99 m ~ 10.89 m
Throw Ratio:	1.49 ~ 1.64
Lamp Power:	210 W
Lamp Life (Normal / SuperEco Mode):	4000 / 10000 (hours)
Brightness (Max.):	3200 ANSI Lumens
Contrast Ratio (Max.):	22000:1
Optical Offset:	116 % +/-5%

AUDIO

Speaker:	10W Cube x1
----------	-------------

INPUT SIGNAL

Video:	480i and 576i, 480p and 576p, 720p, 1080i, 1080p
Frequency (H/V):	15 ~ 100 KHz / 24 ~ 120 Hz

COMPATABILITY

PC:	Support up to 1920x1080@60Hz
Mac:	Support up to 1920x1080@60Hz

CONNECTOR

Digital Input:	HDMI (1.4a) x1 / HDMI (MHL2.0) x1
Audio Input:	3.5mm mini jack x1
Audio Output:	3.5mm mini jack x1
Microphone in:	3.5mm mini jack x1
Control:	RS-232
USB:	Mini type B x1 (Maintenance and mouse control)

POWER

Voltage:	100~240Vac 50/60Hz (Auto Switching)
Power Consumption:	330 W (Max.)
Standby:	<0.5W

OPERATING CONDITION

Temperature:	0°C ~ 40°C (32°F ~ 104°F)
Humidity:	0% ~ 90% (non-condensing)

NOISE LEVEL

Eco Mode:	30dB
-----------	------

DIMENSIONS

Physical:	316 x 228 x 103.7 mm
-----------	----------------------

WEIGHT

Net:	2.4 kgs / 5.29 lbs
------	--------------------

REGULATIONS

Mexico Energy test/Registration, EAC, TUVS Mark(Argentina), India BIS, FCC,CE EMC, CB,CCC, ROHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, RCM, PSB, KC

PACKAGE CONTENTS

Power Cord, 1.8m, black 1 /Remote Control with Batteries (Without Laser pointer) x1 / Quick Start Guide (one sheet version) x1 / ViewSonic CD Wizard (With User Manual) x 1