

ViewSonic® PROJECTOR PX725HD

Key Features

Bold Cinematic Color | Smooth Color
Transitions | Professional Image
Calibration | Powerful Sound | Cinematic
Color Schemes



Product Description

ViewSonic's PX725HD is a 1080p projector with stunning color performance delivered via a 6X Speed RGBRGB color wheel and ViewSonic's exclusive Cinema SuperColor™ technology. PX725HD projects razor-sharp images in incredible Rec. 709 color so you can experience movie scenes with the same cinematic color that the director intended. Personalized image customization is made possible via ISF certified calibration, which enables technicians to fine-tune projector settings to match your usage and preferences. PX725HD's innovative vColorTuner color profile exchange tool takes customization to the next level by allowing users to exchange specially created color profiles to deliver a more versatile cinematic color experience. Updating PX725HD software is made simple via ViewSonic Projector Software Update which is available online and enables you to keep your projector firmware up to date conveniently and easily. Dual HDMI ports and SonicExpert technology allow you to experience excellent HD video and audio in the comfort of your living room, making PX725HD a complete home theatre projection solution.



Visit Us  www.viewsonic.com

SPECIFICATION

Projection system:	0.65" 1080p
Native Resolution:	1920x1080
DC type:	DC3
Brightness:	2000 ANSI Lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	3500/7000
Lamp Watt:	240W
Lens:	F=2.6-2.7, f=22-24mm
Projection Offset:	117.6%+/-10%
Throw Ratio:	1.5-1.65
Image size:	30" - 300"
Throw Distance:	1m-10.0m (100"@3.32m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Eco):	30dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM, HDTV, SDTV
Horizontal Frequency:	15k~102kHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	1
Composite:	1
Audio-in (3.5mm):	1
Audio-in (RCA R/L):	1
HDMI:	2 (Back)

OUTPUT

Audio out (3.5mm):	1
Speaker:	8W Cube
USB type A (Power):	1 (5V/ 1.5A)

CONTROL

RS232:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 310W Standby: <0.5W
Operating Temperature:	5~40°C
Carton:	Color
Net Weight:	2.94kg
Dimensions (WxDxH) w/adjustment foot:	348x234x107mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
Remote Control:	1(w/ backlit)
QSG & CD:	QSG: 1 / CD: NA